

FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 4





FIG. 6

CORE AREA, mm ²	mm/SIDE	IO HEIGHT, μm	IO WIDTH, μm	AREA	MAX IO	WASTED AREA	% OF CORE
10	3.162278	H=188	75	12.51941	169	1.67	13%
		Z=120	108	11.57549	117		
20	4.472136	H=188	75	23.50442	239	2.33	10%
		Z=120	108	22.20423	166		
30	5.477226	H=188	75	34.26025	292	2.83	8%
		Z=120	108	32.68667	203		
40	6.324555	H=188	75	44.89744	337	3.26	7%
		Z=120	108	43.09339	234		
50	7.071068	H=188	75	55.45882	377	3.63	7%
		Z=120	108	53.45171	262		
60	7.745967	H=188	75	65.96634	413	3.97	6%
		Z=120	108	63.77566	287		

FIG. 7






FIG. 8

FUNCTION	FO/SLEW	TYPE	TPLH	TPHL	TP	O/P SLEW
IV110	2SL/0.1ns	8-TRACK	0.2361	0.2143	0.2252	0.29935
		7-TRACK	0.2377	0.2192	0.22845	0.3033
	6SL/0.3ns	8-TRACK	0.4107	0.3535	0.3821	0.4479
		7-TRACK	0.4144	0.3605	0.38745	0.4545
NA210	2SL/0.1ns	8-TRACK	0.2718	0.2549	0.26335	0.3304
		7-TRACK	0.2697	0.2498	0.25975	0.3281
	6SL/0.3ns	8-TRACK	0.4526	0.4113	0.43195	0.493
		7-TRACK	0.4466	0.4027	0.42465	0.4883

FIG. 9